

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 11-276510

(43)Date of publication of application : 12.10.1999

(51)Int.Cl.

A61F 2/28

A61F 2/30

A61L 27/00

(21)Application number : 10-085196

(71)Applicant : KYOCERA CORP

(22)Date of filing : 31.03.1998

(72)Inventor : YOSHIHARA YUSUKE

(54) SURFACE MODIFYING BONE PROTHESIS MEMBER AND METHOD FOR MANUFACTURING THE SAME**(57)Abstract:**

PROBLEM TO BE SOLVED: To provide a surface modifying bone prosthesis member for safely applying to a section where a large shear intensity is added by providing a three-dimensional surface structure, of which ingrowth of a newly generated bone quickly grows and of which density of space occupancy becomes large.

SOLUTION: This surface modifying bone prosthesis member comprises in such a manner that a mixed material, CM chitin sponge 3, which is mixed with CM chitin, a granule of calcium phosphate such as HAP, TCP, and AWGC, is filled into space of a three-dimensional madrepore, beads block 1, formed from a non-absorbent material for an organism such as a wire mesh and a beads-combined body. A method for manufacturing the prosthesis member is shown in such a way that the three-dimensional madrepore 1 or a bone prosthesis member F having the madrepore 1 at a desired part of the surface is soaked into a CM chitin aqueous solution and taken out to rapidly cool.

